




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04R 1/40	A1	(11) International Publication Number: WO 96/14723 (43) International Publication Date: 17 May 1996 (17.05.96)
(21) International Application Number: PCT/NL95/00384 (22) International Filing Date: 8 November 1995 (08.11.95) (30) Priority Data: 9401860 8 November 1994 (08.11.94) NL (71) Applicant (for all designated States except US): DURAN B.V. [NL/NL]; Koxkampseweg 10, NL-5301 KK Zaltbommel (NL). (72) Inventor; and (75) Inventor/Applicant (for US only): DE VRIES, Gerard, Hendrik, Joseph [NL/NL]; Oeverwaluw 23, NL-5221 GM s'-Hertogenbosch (NL). (74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).		(81) Designated States: AU, BG, BR, CA, CN, FI, GE, HU, JP, KR, MX, NO, NZ, PL, RO, RU, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: LOUDSPEAKER SYSTEM WITH CONTROLLED DIRECTIONAL SENSITIVITY



(57) Abstract

Loudspeaker system having various loudspeakers (SP_i , $i = 0, 1, 2, \dots, m$) which are arranged in accordance with a predetermined pattern and have associated filters (F_i , $i = 0, 1, 2, \dots, m$), which filters all receive an audio signal (AS) and are equipped to transmit output signals to the respective loudspeakers (SP_i) such that they, during operation, generate a sound pattern of a predetermined form, wherein the loudspeakers (SP_i) have a mutual spacing (l_i), which, insofar as physically possible, substantially corresponds to a logarithmic distribution, wherein the minimum spacing is determined by the physical dimensions of the loudspeakers used.

Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Loudspeaker system with controlled directional sensitivity

The invention relates to a loudspeaker system comprising various loudspeakers which are arranged in accordance with a predetermined pattern and have associated filters, which
5 filters all receive an audio signal and are equipped to transmit output signals to the respective loudspeakers such that they, during operation, generate a sound pattern of a predetermined form.

10 A loudspeaker system of this type is disclosed in US Patent 5 233 664. The system described in said patent comprises m loudspeakers and N microphones, which are arranged predetermined distances away from the loudspeakers. Each loudspeaker receives an input signal from a separate series
15 circuit of a digital filter and an amplifier. Each of said series circuits receives the same electrical input signal, which has to be converted into an acoustic signal. The digital filters have filter coefficients which are adjusted by a control unit, which receives, inter alia, output signals from
20 the microphones. The loudspeakers are arranged in a predetermined manner. The objective is to be able to generate a predetermined acoustic pattern. During operation the control unit receives the output signals from the microphones and, on the basis of these, adjusts the filter coefficients of the
25 digital filters until the predetermined acoustic pattern has been obtained. Loudspeakers in a linear array, in a matrix form and in a honeycomb structure are described in the embodiments.

The directional sensitivity of the known loudspeaker system can be controlled up to about 1400 Hz for the embodiments with
30 a linear array and a matrix arrangement. An upper limit of about 1800 Hz is cited for the honeycomb structure. This upper limit is inadequate for many audio applications and it would be desirable to provide a loudspeaker system which can control the directional sensitivity up to frequencies of about 10 kHz.

35 In J. van der Werff, "Design and Implementation of a Sound Column with Exceptional Properties", 96th Convention of the AES (Audio Engineering Society), February 26 - March 1, 1994, Amsterdam, an analogue loudspeaker system is described in which

the individual loudspeakers are arranged at non-equidistant spacings along a straight line. The gaps between the individual loudspeakers are calculated on the basis of the criterion of maintaining the side lobes of the acoustic pattern transmitted during operation so as to be at a suitably low level. The density of the number of loudspeakers per unit length is greater in the vicinity of the acoustic centre than at a distance away from this.

The primary objective of the present invention is to provide a loudspeaker system which has a controlled directional sensitivity over as wide a frequency range as possible.

A further objective of the invention is to provide a loudspeaker system wherein the maximum deviation of the directional sensitivity is as far as possible constant over the envisaged frequency range.

To this end, the invention provides a loudspeaker system according to the type described above, characterised in that the loudspeakers have a mutual spacing, which, insofar as physically possible, substantially corresponds to a logarithmic distribution, wherein the minimum spacing is determined by the physical dimensions of the loudspeakers used. By not making the mutual spacing of the loudspeakers equidistant but adapting it to the frequency requirements, it is possible to control the directional sensitivity up to, certainly, 8 kHz. The side lobe level is reduced at the same time. By choosing a logarithmic distribution, the maximum deviation of the directional sensitivity over the envisaged frequency range is kept as constant as possible and spatial aliasing at higher frequencies is counteracted. Primarily it is not so much the form of the sound pattern as the transmission angle which is controlled.

There are various possibilities for the arrangements. For instance, the loudspeakers can be arranged along a straight line, in which case the said distribution extends from a central loudspeaker in one direction along said line.

As an alternative, the loudspeakers can be arranged along two straight line sections, in which case the said distribution extends from a central loudspeaker in two directions along the two line sections, which central loudspeaker is located at an

intersection of the two line sections.

The two line sections can be on a straight line.

As a further alternative, the loudspeakers can be arranged on two lines which cross one another or can be arranged in the
5 form of a matrix.

Preferably, the loudspeakers are identical.

The loudspeakers can be arranged in various rows, each of which is optimised for a specific, predetermined frequency band. The loudspeakers arranged in said rows can, for example,
10 be of different dimensions and/or have a different logarithmic distribution.

The filters can be FIR filters or IIR filters.

Preferably, the filters are digital filters which have predetermined filter coefficients and are each connected in
15 series with associated delay units having predetermined delay times, which filter coefficients and delay times are stored in a memory, for example an EPROM.

The audio signal preferably originates from an analogue/digital converter, which also has an input for
20 receiving a background signal corresponding to the sound in the surroundings. Said analogue/digital converter can be provided with an output for connection to at least one dependent ancillary module.

The invention will be explained in more detail below with
25 reference to a few diagrammatic drawings, in which:

Figure 1a shows an effective, normalised array length as a function of the angular frequency for a distribution of three loudspeakers per octave band;

Figure 1b shows the deviation of the opening angle α as a
30 function of the angular frequency for a distribution of three loudspeakers per octave band;

Figures 2a to 2d show various arrangements of loudspeakers in accordance with the present invention;

Figure 3 shows a diagrammatic overview of an electronic
35 circuit which can be used to control the loudspeakers; and

Figure 4 shows an example of an acoustic pattern.

The present description refers to an array of loudspeakers. Such an array can be one-dimensional (line array) or two-

dimensional (plane).

If the transmitting portion for each frequency component in a sound signal which is reproduced is proportional to the wavelength of the frequency component concerned, the array is found to display frequency-independent behaviour. Two concepts are important for good understanding of the present invention: the opening angle and the transmission angle. The opening angle is, by definition, the angle through which a sound source can be turned such that the sound pressure does not fall by more than 6 dB with respect to the maximum value which is measured at a fixed point in a plane in which the sound source is located, and at a distance which is large compared with the physical dimensions of said sound source. Said angle is indicated by " α " in Figure 4, which figure will be discussed further below. The transmission angle is, by definition, the angle θ which the axis of symmetry of the transmission pattern makes with a plane perpendicular to the axis along which a one-dimensional array is arranged, or with a middle vertical line of the plane in which a two-dimensional array is arranged (Figure 4). In the case where a two-dimensional array is used, two opening angles and two transmission angles can be defined for a transmission pattern.

The following relationship applies for the dimensions of the effective portion of a linear array having an infinite number of loudspeakers, as a function of the frequency:

$$l(\omega) = k \cdot \lambda = \frac{c_0 \cdot 2 \cdot \pi}{\omega} \quad (1)$$

where: $l(\omega)$ = the effective array size,
 c_0 = the speed of sound (m/s)
 k = a proportionality constant, which is a measure of the opening angle α
 ω = angular frequency (rad/s)

The following rule of thumb can be used to calculate the proportionality constant k :

$$k = \frac{72^\circ}{\alpha} \quad (2)$$

where: α is the desired opening angle in degrees.

This relationship for the proportionality constant k has an accuracy of more than 90 % for $k > 1$.

Because an array in practice does not consist of an infinite number of loudspeakers but is composed of a limited number of loudspeakers, the array size $l(\omega)$ is quantised. As can be seen from Figures 1a and 1b, this results in a limited resolution in the opening angle α . Figure 1a shows the effective array length (logarithmic) as a function of the angular frequency (logarithmic 1/3 octave) for a distribution of three loudspeakers per octave band. Figure 1b shows the deviation of the opening angle α as a function of the angular frequency for a distribution of three loudspeakers per octave band. Of course, this is merely an example and the invention is not restricted to three loudspeakers per octave band.

The criterion taken for calculation of the spacing of loudspeakers is that the maximum deviation of the directional sensitivity must be kept as constant as possible over the envisaged frequency range. As will become apparent below, this can be achieved by providing the loudspeakers used, SP_1 , SP_2 , ..., with a logarithmic arrangement with respect to a central loudspeaker SP_0 . This also results in minimisation of the deviation of the opening angle α and minimisation of the number of loudspeakers required.

The frequency-dependent variation in α is inversely proportional to the number of loudspeakers per octave band and theoretically is 50 % for a distribution of one loudspeaker per octave. Preferably, in practice use is made of at least two to three loudspeakers per octave.

If the array size $l(\omega)$ in a single dimension is quantised with the aid of n steps per octave band, the following relationship then applies for the array size:

$$l(i) = k \cdot \frac{C_0 \cdot 2 \cdot \pi}{\omega_{\min} \cdot 2^{\frac{i}{n}}} \quad \text{where } 0 \leq i \leq n_{\max} - 1 \quad (3)$$

where: ω_{\min} = the lowest reproducible angular frequency (radians per second) at which the opening angle α is still controlled;

n = number of loudspeakers per octave band;

n_{\max} = the total number of discrete steps in a single dimension, depending on the desired frequency range.

For a value of $i = 0$, this gives the maximum physical dimension of the array, which is dependent on ω_{\max} and $k(\alpha)$.

The loudspeaker positions depend on the physical configuration of the array. Said configuration can be asymmetrical or symmetrical. In the case of an asymmetrical configuration, the central loudspeaker SP_0 is located at one side of the array, as is shown in Figure 2a. The above Equation 3 applies for the distance $l(i)$ between the loudspeaker positions and the central loudspeaker SP_0 , which corresponds to a logarithmic distribution. In order to produce such an array, n_{\max} loudspeakers are required in one dimension.

Figure 2b shows a symmetrical arrangement of loudspeakers around a central loudspeaker SP_0 , which is located in the middle. The above Equation 3 multiplied by a factor of $1/2$ applies for loudspeakers SP_1, SP_2, SP_3, \dots , whilst Equation 3 multiplied by a factor of $-1/2$ applies for loudspeakers $SP_{-1}, SP_{-2}, SP_{-3}$. For a symmetrical arrangement according to Figure 2b, $2 \cdot n_{\max} - 1$ loudspeakers are needed. It is found that the symmetrical arrangement according to Figure 2b gives a better suppression of the side lobe level than does the asymmetrical arrangement according to Figure 2a.

In fact, Figure 2b is a combination of 2 array configurations according to Figure 2a with coincident central loudspeakers. These two separate loudspeaker arrays can also be located on two line sections, which do not lie in the extension of one another.

Instead of the configurations shown in Figures 2a and 2b, two-dimensional configurations are also possible. Figure 2c shows a matrix arrangement of loudspeakers, in which various loudspeaker arrays according to Figure 2b are arranged parallel to one another. $n_{\max \text{ hor}} \cdot n_{\max \text{ vert}}$ loudspeakers are present in an arrangement of this type. Here $n_{\max \text{ hor}}$ is the number of loudspeakers in the horizontal direction and $n_{\max \text{ vert}}$ is the number of loudspeakers in the vertical direction.

Figure 2d shows a two-dimensional configuration with an

arrangement in the form of a cross. Figure 2d shows two loudspeaker arrays according to Figure 2b which are arranged perpendicular to one another with a coincident central loudspeaker $SP_{0,0}$. $n_{\text{max hor}} + n_{\text{max vert}} - 1$ loudspeakers are present in the arrangement according to Figure 2.

Of course, arrangements along other and more lines crossing one another are also possible. The only proviso in the context of the present invention is that the various loudspeakers $SP_{i,j}$ are arranged in accordance with a logarithmic distribution, for example as defined by the above Equation 3.

In practice, the loudspeakers have a definitive physical size. This physical size determines the minimal possible spacing between the loudspeakers. Those loudspeakers which, in accordance with the above Equation 3, would have to be placed a distance apart which is smaller than the physical size permits are, in practice, placed in contact with one another. This leads to concessions with regard to the resolution in the frequency range concerned. Naturally, the concessions with regard to the resolution are as small as possible if the sizes of the loudspeakers are chosen to be as small as possible. However, smaller loudspeakers usually have poorer characteristics with regard to power and efficiency. Therefore, in practice, a compromise will always have to be made between the quality of the loudspeakers and the concessions in respect of the resolution.

Preferably, all loudspeakers must have the same transfer function. Therefore, all loudspeakers in the one-dimensional or two-dimensional array are preferably identical to one another.

It is, however, also possible to use various arrays arranged alongside one another which are provided with different loudspeakers, in which case the dimensions of the loudspeakers and their mutual positions in the various arrays are optimised for a specific limited frequency band. In that case no concessions have to be made in respect of the resolution and the power or the efficiency. Of course, this is at the expense of the number of loudspeakers required.

Figure 3 shows a diagrammatic overview of a possible electrical circuit for controlling the loudspeakers. For ease,

only the loudspeakers SP_0, SP_1, \dots, SP_n and the associated electronics are indicated in the figure. Therefore, Figure 3 corresponds to the loudspeaker array according to Figure 2a. However, similar electronic circuits also apply for other loudspeaker arrays according to the invention, for example according to Figures 2b, 2c and 2d.

Each loudspeaker SP_i receives an input signal from a series circuit comprising a filter F_i , a delay unit D_i and an amplifier A_i . The filters F_i are preferably digital filters of the FIR (Finite Impulse Response) type or of the IIR (Infinite Impulse Response) type. If IIR filters are used, they preferably have a Bessel characteristic. The coefficients of the filters F_i are calculated beforehand and stored in a suitable memory, for example an EPROM. This preferably takes place during manufacture of the loudspeaker system. The filter coefficients of the filters F_i are then no longer adjusted during operation, so that it is then possible to dispense with an electronic control unit which would be connected to the filters F_i and the delay unit D_i for adjusting the filter coefficients, or the delay times, during operation on the basis of the sound pattern recorded by microphones. However, use of such a feedback to a control unit (not shown here) and various microphones, as is disclosed in the abovementioned US Patent 5 233 664, is possible within the scope of the present invention.

The delay times for each of the delay units D_i are preferably also calculated beforehand during manufacture and stored in a suitable chosen memory, for example in an EPROM. These delay times are then also no longer changed during operation.

Each of the filters F_i receives an audio signal AS via a first output $S_{0,1}$ of an analogue/digital converter ADC. The analogue/digital converter ADC receives a first analogue input signal $S_{1,1}$, which has to be converted by the loudspeakers SP_0, SP_1, \dots , into a sound pattern with a predetermined directional sensitivity.

Preferably, the analogue/digital converter ADC is also connected to a measurement circuit which is not shown, which supplies a second input signal $S_{1,2}$ which is a measure for the

analogue/digital converter ADC and using the same sampling frequency for calculation of the filter coefficients as well. The delay units D_i are fed at a sampling frequency of 96 kHz by doubling the first-mentioned sampling frequency. This gives a
5 resolution of 10.4 microseconds. Of course, other sampling frequencies are also possible within the scope of the invention.

A loudspeaker array designed in accordance with the guidelines given above has a well defined directional
10 sensitivity which is substantially frequency-independent over a wide frequency range, that is to say up to at least a value of 8 kHz. The directional sensitivity is found to be very good in practice.

It is also possible to design a loudspeaker array in
15 accordance with the guidelines given above with which the transmission pattern is not perpendicular to the axis along which the loudspeaker array is located (or the plane in which said array is located). The opening angle α can be selected by making a suitable choice for the filter coefficients, whilst
20 any desired transmission angle β can be obtained by adjustment of the delay times. In this way, a sound pattern can be directed electronically. When a one-dimensional loudspeaker array is used, the transmission pattern is rotationally symmetrical with respect to the array axis 2. When a two-
25 dimensional loudspeaker array is used, the transmission pattern is symmetrical according to a mirror image about the array plane. This symmetry can advantageously be used in situations in which the directional sensitivity of the sound which is generated at the rear of the loudspeaker array also has to be
30 controlled.

Finally, Figure 4 shows an example of a (simulated) polar diagram to illustrate a possible result of a loudspeaker array designed according to the invention. The opening angle α shown in this figure is approximately 10° , whilst the transmission
35 angle β is approximately 30° . The arrangement of the loudspeaker array which generates the pattern shown is likewise shown diagrammatically. For the sake of convenience, the logarithmic distribution has been dispensed with in this

WO 96/14723

PCT/NL95/00384

11

diagram.

7. Loudspeaker system according to one of the preceding claims, characterised in that the loudspeakers (SP_i , $SP_{i,j}$) are identical.

5 8. Loudspeaker system according to Claim 1, characterised in that the loudspeakers (SP_i) are arranged in various rows, each of which has been optimised for a specific, predetermined frequency band.

10 9. Loudspeaker system according to one of the preceding claims, characterised in that the filters (F_i) are FIR filters or IIR filters.

15 10. Loudspeaker system according to one of the preceding claims, characterised in that the filters (F_i) are digital filters which have predetermined filter coefficients and are each connected in series with associated delay units (D_i) having predetermined delay times, which filter coefficients and delay times are stored in a memory, for example an EPROM.

20

11. Loudspeaker system according to one of the preceding claims, characterised in that the audio signal (AS) originates from an analogue/digital converter (ADC), which also has an input for receiving a background signal (S_{12}) corresponding to
25 the sound in the surroundings.

12. Loudspeaker system according to Claim 11, characterised in that the analogue/digital converter (ADC) also has an output (S_{02}) for connection to at least one dependent ancillary module
30 (NM).

1/4

fig -1a




fig -1b




fig-2a




fig-2b





fig-2c



3/4

fig-2d






fig-3



4/4

fig-4



INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 95/00384

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04R1/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,5 233 664 (YANAGAWA ET AL.) 3 August 1993 cited in the application see column 1, line 1 - column 3, line 4; claims 1,7,11,14; figures 1,2	1
A	GB,A,2 273 848 (PIONEER ELECTRONIC CORP.) 29 June 1994 see page 1, line 1 - page 5, line 14; claim 1; figures 1,2	1
A	DE,A,35 06 139 (AUSLÄNDER, LUDENDORFF) 5 June 1986 see figure 2	1

	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 February 1996

Date of mailing of the international search report

08.03.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel.: (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

De Haan, A.J.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 95/00384

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO,A,94 01981 (ADAPTIVE AUDIO LIMITED) 20 January 1994 see page 1, line 1 - page 5, line 18; claim 1</p> <p>-----</p>	1

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter Application No
PCT/NL 95/00384

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5233664	03-08-93	JP-A- 5041897	19-02-93
		DE-A- 4205037	11-02-93
		GB-A, B 2259426	10-03-93
GB-A-2273848	29-06-94	JP-A- 6062488	04-03-94
DE-A-3506139	05-06-86	NONE	
WO-A-9401981	20-01-94	EP-A- 0649589	26-04-95
		GB-A- 2284130	24-05-95
		JP-T- 7508625	21-09-95

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.